

Ultra PREMIUM EX-350

For xing Tiles, Marbles, Granites & others stones on interior oor & wall.

Product Description:

It is polymer modied cement based quick set tile adhesive specially des igned for heavy duty applicants for xing vitried tiles, slabs, natural stones and large size tiles on interior wall and oor surfaces. Not recommended for exterior were direct sunlight come.

Temperature and water resistant

Very good adhesion

Non toxic

Water cleanup of un cured adhesive

Very easy to apply

Dual purpose for wall and oor

High bond strength

Economical

Direction & Instruction for use:

Add 5 litter clean water with 20kg of Ultra BOND PREMIUM EX 350 and stir well until a lump free compound is achieved. The surface to be tiled should be clean and sound. Old surfaces must be free from any kind of grease oils wax etc. At site addition of water shall be adjusted to attain desired consistency and mix thoroughly until a homogeneous paste is obtained. Allow tiling to set for 24 hours prior to lling joints.

Packing:

Ultra BOND Premium EX-350
available in 20kg bags



Product Application:

Apply Ultra BOND EX 350 evenly on the substrate. Use a notched trowel to have a uniform thickness 3mm minimum. Apply the tiles on the substrate and press them rmly, while making sure that the paste does not slip from the tile sides. Ultra Bond EX 350 can also be applied on the back of tiles to ensure full adhesion with all the surface. In case exceptional performance is required.

TECHNICAL DATA compliant with Ultra BOND EX-350 quality standard	
Appearance	Powder
Composition	Cement, Siliceous sand & Additives
Color	Grey & White
Density	1 ± 0.05
Mixing water for use a slurry key	5L/1 bag 20kg
Open Time	25 minutes
Adjustability	45 minutes
Foot Traffic	24 hours
Interval Before Normal Use	14 days
Voc	<1 g/L (USEPA 24)
Grouting	24 hours
Coverage	1 bag= 20kg/ 4.8m ² in 3mm thickness
Shelf life	12 months of the original packing in dry environment

Precautions:

Apply Ultra BOND EX 350 on the substrate by areas of around 1 m² each, which can be tiled within a maximum of 25 minutes from application time at 23°C. After that time, an outer skin may form thus preventing the tile from adhering properly to Ultra BOND EX 350. Adjustments to the tiles should only be made during Ultra BOND EX 350 open time. It is recommended to leave a minimum width of 2 mm around the tiles. Grouting the tile joints should only be done at least 24 hours after tiling, using Ultra Joint Filler EX-20.

Coverage:

Ultra BOND EX 350 20kg gives coverage of 4.8 m² in 3 mm thickness.

Shelf Life:

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

Packing:

Ultra BOND PREMIUM EX-350 available in 20kg bags.

Safety Measures:

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, Protective clothing such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidental swallowed, do not induce vomiting, but call for medical assistance immediately. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

CLEANING:

Clean the tools with water after use. Cured materials can only be removed mechanically.

Manufactured & Marketed By:

يتم تصنيعها وتسويقها بواسطة:

ULTRA ADHESIVES IND. L.L.C الترا لصناعة مواد اللصق ذ.م.م

P.O Box : 2219, UAQ-UAE. Tel: +971 67670988

ص ب : 2219، أم القيوين - ا.ع.م هاتف : +971 67670988

Email : info@ultraadhesive.com

Web: www.ultraadhesive.com

AUSTRALIA • INDIA • K S A • MALDIVES • MOGADISHU • OMAN • U A E

Our Group of Companies

PEGAD
ADHESIVES & COMPOUNDS

Regency BOND
ADHESIVES & COMPOUNDS

Ultra FILL